

SPS-300 Series

Advanced ECRs From The World's Leading ECR Builder

Features

- Choose a flat keyboard model for food service or a raised keyboard model for retail environments.
- On screen programming simplifies setup and makes changes easy to manage after installation.
- Connects to popular POS peripherals.
- Interconnect multiple units to consolidate your sales and share access to peripherals.



SAM4s SPS-340 shown with optional card reader.



SPS-320
Flat Spill-Resistant Keyboard;
Receipt Printer




SPS-340
Flat Spill-Resistant Keyboard;
Receipt And Journal Printers



SPS-345
Raised-Key Keyboard (Expanded);
Receipt And Journal Printers

Best Applications

- Food Service: Quick Service, Sandwich, Deli, Kiosks, Cafeteria, Ice Cream
- Independent Retail Merchants, Especially Retail Scanning
- Simple Franchise Concepts
- Parks, Stadiums, Convention Centers And Other Venues With Many Concession Locations



* PENDING APPROVAL

Operator Screen

The large, bright operator screen clearly sets the SPS-300 series apart from traditional ECRs. Just glance at the screen to verify or fill an order. If necessary, you can page up or down through larger transactions. Easy-to-follow messages guide your operator with minimal training.

On screen programming simplifies programming of new PLU items and price changes. Managers can access sales, inventory and financial information and view it directly on the screen.

Keyboard

The programmable keyboard can be customized with PLU keys for open price or preset entries and function keys for discounts, payments and corrections.

- Models with the 150 key position flat keyboard support 100 or more PLU locations.
- The raised keyboard model features 21 standard PLU locations, expandable to 63 or more PLU locations.

Thermal Printer

Keep pace with fast, quiet, thermal printing. Drop-in loading simplifies paper changing and virtually eliminates paper jamming.

Electronic Journal

The SPS-300 stores your detailed sales journal in memory for printing at the end of the day. Electronic journal can be printed in its entirety or select from ten different print option selections.

Secure SD Port

Save/load your program, load receipt logos/images or update firmware by SD card.

Communications Ready

Two RS-232C ports and inter-register communications (IRC) are available on every SPS-300 series ECR. Using IRC, up to 8 registers can be connected for consolidating store wide reports and/or programming. Each RS-232C port and two optional, additional ports can be connected to one of the following options: direct or modem PC communications with optional polling software; kitchen printer; slip printer; scale; scanner; pole display; coin dispenser; Datatran™ integrated credit; kitchen video; video surveillance.

Additional Features

- Up To 5 Price Levels For Each PLU
- Up To 5 PLU Modifier Keys
- Approximately 20,000 PLUs For Large Item Or UPC Files
- Automatic Tax Computation For Up To 4 Rates Or Tables
- 10 Media Keys: Cash, Check And Up To 8 Charge Keys
- Up To 99 Group Totals
- Up To 99 Clerks/Cashiers
- Graphic Bitmap Logo
- Condensed Journal
- Compulsory Cash Declaration
- Hash PLU Status
- 10 One-Touch Macro Keys
- Training Mode

Management Reports

- Complete Financial Report
- Individual Clerk/Cashier Report
- Hourly Sales Analysis
- Reporting For Up To 99 Clerks/Cashiers
- PLU, Group And Stock Reports
- Period-To-Date Financial, Hourly, Cashier, Group And PLU Reports
- Sales By Day Report For 31 Days
- Open Check Report



Eight-Line By 32-Character LCD Operator Screen



9-Digit LED Customer Turret Display



SD Port Hidden Under The Printer Cover Is Secure From Tampering



Up To 4 RS-232C Ports Hidden Behind A Convenient, Easy To Access Door



2 Media Slot Drawer With Extra Deep Insert And Adjustable Coin Dividers

SPECIFICATIONS

Display:	8-Line x 32 Character Backlit Liquid Crystal Operator Display
Rear Display:	9-Digit LED
Printer(s):	Seiko LTPD245
Printer Speed:	22 Lines Per Second
Paper Roll:	2¼" (58mm) Thermal Paper
Dimensions:	15-3/4"W x 11-13/16"H x 17-3/4"D
Weight:	Single Station – 24.76 lbs.; Dual Station – 25.64 lbs.
Power Requirements:	120V AC ± 10%, 50/60 Hz
Power Consumption:	Approximately 25 Watts
Operation Temp.:	32°F ~ 112°
Humidity Range:	30% to 80% RH (Non-Condensing)
Memory Protection:	Full Charge For 24 Hours Will Protect Memory For 90 Days



All product features are subject to change without notice. All product and company names are trademarks, service marks or registered trademarks of their respective owners.